

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
12 September 2003 (12.09.2003)

PCT

(10) International Publication Number
WO 03/075555 A1(51) International Patent Classification⁷: **H04N 3/15**

(72) Inventors; and

(21) International Application Number: **PCT/IL03/00126**(75) Inventors/Applicants (for US only): **MIKKELSEN, Sindre** [NO/NO]; Jens Bjelkes gate 64 A, N-0652 Oslo (NO). **ORSKAUG, Terje** [AU/AU]; 1805/3 Herbert St., St. Leonards, Sydney, New South Wales 2065 (AU).

(22) International Filing Date: 18 February 2003 (18.02.2003)

(25) Filing Language: English

(74) Agent: **REINHOLD COHN AND PARTNERS**; P.O.B. 4060, 61040 Tel Aviv (IL).

(26) Publication Language: English

(30) Priority Data:
148555 7 March 2002 (07.03.2002) IL(71) Applicant (for all designated States except US): **IDEAS ASA** [NO/NO]; Veritasveien 9, P.O.Box 315, N-1323 Hovik (NO).


(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for MW only): **BUTNARO, Sharona** [IL/IL]; Daniel 24, 59397 Bat-Yam (IL).

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: READOUT CIRCUIT FOR AN ACTIVE PIXEL IMAGE SENSOR



(57) Abstract: A readout circuit (29) for reading active pixels in a sensor (10) having at least one sensor segment (11) each containing addressable pixels (12) includes a respective sample and hold unit (28) for sampling and holding an analog value associated with a corresponding pixel, and an analog multiplexer (35) in each segment having an addressable channel coupled to each sample and hold unit for carrying the corresponding held value of the respective pixel. A lookup table (38) stores addresses of predefined neighboring pixels associated with the respective pixel. An encoder (36) is responsive to one or more trigger signals for generating an address in the lookup table, and a controller (37) feeds the address to the lookup table and successively feeds the addresses of the predefined neighboring pixels output by the lookup table to the analog multiplexer.

WO 03/075555 A1